

PAWO F1 - Wire Ropes for Speed Governors








Special rope for speed governors

Product info

To achieve proper operation, a variety of ropes of ropes is required to match the many different requirements of overspeed governors.

Technical data

Please see the table below for a survey on the ropes most commonly used.

rope diameter (mm)	part-no.	surface	calculated mass (kg/m)	min. breaking load (kN)	Construction	
	6,0	581306011	U	0,126	21,0	6 x 19 S - SFC 1770 U sZ
	6,0	585306011	B	0,126	21,0	6 x 19 S - SFC 1770 B sZ
	6,5	591306510	U	0,160	25,8	6 x 19 W - NFC 1770 U sZ
	6,5	595306510	B	0,160	25,8	6 x 19 W - NFC 1770 B sZ
	6,5	591306530	U	0,180	31,0	6 x 19 W - WSC 1770 U sZ
	6,5	595306530	B	0,180	31,0	6 x 19 W - WSC 1770 B sZ
	8,0	591308030	U	0,280	47,0	6 x 19 W - WSC 1770 U sZ
	6,5	741306531	U	0,170	29,7	8 x 19 W - IWRC 1770 U sZ
	6,0	585306030	B	0,150	25,8	6 x 19 S - WSC 1770 B sZ